



FIRE LUBRICANTS

FIRE AP-2 & AP-3 GREASE

Premium quality lithium soap based all purpose grease, fortified with EP additives. It is specially formulated to enhance lubrication interval, **up to 30,000 km under ideal road condition**. It has good thermal, chemical and structural stability including water wash out properties. It provides excellent lubrication and protection to the bearing parts over a wide temperature & pressure range, under normal as well as adverse mechanical conditions.

Product Features & Benefits:

- Good water repellency & surface adhesion.
- Excellent rust protection and resistance to oxidation.
- Lubricates and protects the components for a longer period.
- Excellent structural stability.
- High load carrying capacity & Superior tackiness
- Optimum lubrication, even under adverse mechanical conditions

Application:

Recommended for Lubrication of plain as well as anti-friction bearings in automotive, earth moving equipment, mining equipment and general industrial machineries, Heavy duty ball and roller bearings of steel rolling mills, Universal joints and spline shafts working under heavy torque or with acute transmission angles and bearings.

Performance Level:

IS 7623 - 1993, NLGI- 3 specifications.

Packing Sizes:

180kg, 18 kg, 5kg,3kg,2kg,1kg,500gm, 200gm.

Specification:

CHARACTERISTICS

Sr.No.	Properties	ALL PURPOSE GREASE	
		AP 2	AP 3
1	Consistency of worked grease at 25+/- 0.5°C (60 double strokes)	265 – 295	220 - 250
2	Drop point, ° C,min	180	180
3	Soap Type	Li	Li
4	Structure	Smooth & Buttery	Smooth & Buttery
5	Colour	Lemon yellow	Lemon yellow

Note : The above specification are subject to change without any prior notice & it implies no liabilities or other legal responsibility on our part or third party.