



FIRE LUBRICANTS

Fire Hydrolife

Premium quality very high viscosity index antiwear hydraulic oil specially formulated for use in hydraulic systems which operate over wide temperature range. It also contains antioxidants, antiwear and antifoaming additives.

Product Features & Benefits:

Protect Engine from wear & corrosion, Good metal contact properties which create a protective film over the surface of the operating system and high resistance capacity to corrosion & foaming into the system.

Application:

Recommended for all new generation high and low temperature hydraulic systems. The product can also be used in circulation systems, bearing systems, machine tools and gear cases which operate over wide temperature range due to their improved viscosity/ temperature properties.

Performance Level:

IS: 3098 – 1983 (Reaffirmed 1993)

Packing Sizes:

210, 50, 20ltrs.

Specification:



CHARACTERISTICS

Sr.No.	Properties	Fire Hydrolife							
		32	46	68	100	150	220	320	460
1	Kin.Viscosity cSt @ 40°C	29 - 33	43 – 48	64 - 72	95 -105	145- 155	210 -230	315 -350	440– 480
2	V.I.(min)	95	95	95	90	90	90	90	90
3	Flash Point (COC) ^o C ,min	190	200	210	220	230	230	230	230
4	Pour Point (COC) ^o C ,max	-3	-3	-3	-3	-3	-3	-3	-3
5	Rust (ASTMD 665,24/Hrs)	β-----Passes-----à							

Note : The above specification are subject to change without any prior notice & it implies no liabilities or other legal responsibility on our part or third party.