



FIRE LUBRICANTS

Fire Gear EP-90/140/80W

Premium quality extreme pressure **EP Type GL-4** gear lubricating oils, blended from high viscosity index base oil with selected extreme pressure additives, to provide antifoam, antiwear and antirust properties to ensure good film presence and optimum lubrication between gears teeth's during operation and prevent scuffing and scoring of gears.

Product Features & Benefits:-

- Excellent thermal & oxidation stability.
- Free from any suspended matter, grit, water or any other impurities.
- Long service life even after high temperature operation.
- Anti foaming and good film forming.
- Smooth gear changing/shifting and long oil drain period interval.
- Prevent scuffing and scoring of gears

Application:

Suitable for Hypoid, spiral bevel, spur and double reduction constant or synchromesh gear boxes, transfer boxes etc. of vehicles and construction plants; steering boxes and oil lubricated universal gear joint.

Performance Level:

IS 1118-1992 (EP TYPE GL-4),
US MILITARY MIL-L-2105, API: GL-4 specifications.

Packing Sizes:

210, 50, 20, 10, 5, 1, 500ml.

Specification:

Properties	EP-90	EP-140	EP-80W
Appearance	Golden	Golden	Golden
Kinematic Viscosity, cSt@ 100° C	17 - 20	28 – 34	8 - 10
Viscosity Index (Min)	90	90	95
Pour Point, °C, max.	-9	-6	-25
Flash Point, COC, °C, min.	220	220	180

Note : The above specification are subject to change without any prior notice & it implies no liabilities or other legal responsibility on our part or third party.