



FIRE LUBRICANTS

Fire Super - 40

High quality, heavy duty **monograde** engine oil, meeting API: SC/CC performance. It is blended with selected highly base oils and special additives with antioxidant, antiwear, anticorrosion, detergent, dispersant and antifoam agents; to suit petrol and diesel engines.

Product Features & Benefits:-

High detergency level & excellent oxidation stability.
Ease in cold starting and can be used in all climate condition.
Optimum viscosity range for running new and old engines.
Ensure minimum top-ups, reduced ring wear
Ensure engine cleanliness, and longer battery life.
Provides longer engine life & oil drain period

Application:

Suitable for **turbo charged diesel engines**, naturally aspirated diesel engines & gasoline engines, operating with high ring zone temperatures, under severe duty conditions.

Performance Level:

IS 13656-2002 (E-PL1/E-DL1), US MILITARY MIL-L-2104B and API: SC/CC specifications.

Packing Sizes:

210, 50, 20, 10, 7.5, 6, 5, 1, 500ml.

Specification:

CHARACTERISTICS

Sr.No.	Properties	Fire Super - 40
		SAE GRADE 40
1	Kin. Viscosity cSt @ 100°C	13.0 – 15.0
2	V. I. (min).	95
3	Flash point (COC) °C, Min.	220
4	Pour Point, (COC) °C, Max.	(-) 6
5	TBN mg KOH/gm	5.0 – 7.0

Note : The above specification are subject to change without any prior notice & it implies no liabilities or other legal responsibility on our part or third party.