



ISO 9001:2000

FIRE LUBRICANTS

Fire Turbo 15w/40

Premium multigrade engine oil developed for new generation heavy duty diesel engines. It is blended with high quality base oils and special additives for good anticorrosion, antirust an antioxidation and antiwear property assists quicker engine start, longer battery life & increased fuel efficiency.

Product Features & Benefits:-

Enhanced power and protection to Turbo Charged Engines
Ensure minimum top-ups, reduced ring wear & excellent TBN stability.
Reduced engine deposits with reduced wear and carbon build up.

Application:

Special dispersant additives provides excellent piston cleanliness and complies with EURO-II and EURO-III technologies suitable for mixed fleet of petrol engines, diesel engines and turbocharged diesel engines.

Performance Level:

IS13656-2002(E-DL5/E-PL4) API: CH-4/SL & MB228.3

Packing Sizes:

210, 50, 50, 10, 7.5, 5, 1.

Specification:

SAE GRADE	15W- 40
Kinematic Viscosity cSt @ 100°C	13.5 – 15.5
Viscosity Index, Min.	135
TBN mg KOH/gm	11 - 13
Flash point (COC) °C, Min.	200
Pour Point °C, Max.	(-) 24

Note : The above specification are subject to change without any prior notice & it implies no liabilities or other legal responsibility on our part or third party.